

*Additives for Asphalt*

# NUMIXER™ Technical Sheet

## Typical Properties

| Property                          | Value |
|-----------------------------------|-------|
| Moisture, Vacuum Oven, typical, % | 2.0   |
| Specific Gravity, typical, lb/gal | 7.5   |
| Viscosity @ 75°F, typical, cps    | 65    |
| Iodine Value, typical             | 115   |
| Flash Point, typical, COC, °F     | >400  |
| Sulfur, typical, ppm              | <50   |
| Insolubles, typical, %            | 1.5   |

## Packaging

| Property | Value  |
|----------|--|
| Form     | Pumpable liquid in Bulk truck or railcar       |
|          | Drums, totes available by special request only |

*All values representative only*

Sripath® NuMIXER™ is regarded as non-hazardous when used in accordance with conventionally accepted industrial hygiene & handling practices. Please refer to MSDS for specific recommendations on safe handling & use.

DISCLAIMER: Although all statements and information contained herein are believed to be accurate and reliable, they are presented without guarantee or warranty of any kind, express or implied. Information provided herein does not relieve the user from the responsibility of carrying out its own tests and experiments, and the user assumes all risks and liability for use of the information and results obtained. Statements or suggestions concerning the use of materials and processes are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all toxicity data and safety measures are indicated herein or that other measures may not be required.

© 2020 Sripath Technologies®, LLC