

# NuMIXER®

### Bitumen Softener A Blend of Bio-Based Oils

## Roofing

NuMIXER adds flexibility to compounds to better accommodate thermal and physical stresses to reduce cracking. It enhances adhesion to a variety of substrates.



# Paving

NuMIXER enhances low temperature and penetration properties. It improves fracture toughness and fatigue resistance of roadways. It is compatible with a wide range of bitumens.



### A green, all-natural bitumen softener

NuMIXER<sup>®</sup> is an all-natural blend of prime bio-oils designed to enhance the properties of bitumen in roofing and paving applications.

NuMIXER is used to improve low temperature properties, enhance the compatibility and dispersion of polymer and crumb rubber in bitumen, and reduce and manage viscosity. It delivers roadways with better performance and long-term durability. It decreases stiffness and increases the m-Value in poor quality binders while improving failure, fatigue, and cracking resistance in mixes and pavements.

For roofing applications, NuMIXER improves cold ductility, flexibility, and adhesion to substrates. By lowering the viscosity, it allows formulations to accept enhanced filler loadings.

NuMIXER has a very low odor and no VOCs, promoting worker safety and ease of use.

**Polymer Compatibilizer** 

Low Temperature Aid

**Viscosity Modifier** 

**Easier Processing** 

#### **Better Durability**



### NuMIXER® Technical Data

Property	Typical Value	
Moisture, Vacuum Oven	2 %	
Density	o.9 kg/liter	7.8 lb/gal
Viscosity @ 24 °C (75 °F)	0.05 Pa.s	50 cp
lodine Value	115	
Flash Point, COC	> 204 °C	> 400 °F
Sulfur	< 50 ppm	
Insolubles	1.5 %	

**PHYSICAL CHARACTERISTICS:** NuMIXER is a blend of bio-based oils derived from harvested crop. The viscosity and color are influenced by a multitude of natural factors and can vary over time. However, the product is formulated to always perform as intended and to consistently deliver desired properties and performance.



Sripath.com Americas & Africa



Sripathapc.com Australia, New Zealand, & Asia-Pacific Region



SripathInnovations.com

United Kingdom, European Union,

& Middle East



Bitpath.co.in



COPYRIGHTS: ©-2025 Sripath Technologies®, LLC

TRADEMARKS: Sripath®, Sripath Technologies®, the Sripath Technologies Logo®, RELIXER®, PGXpand®, PGXtend®, NuMIXER®, RENUBIT®, SriCote®, KoolTEQ™, PHALANX®, Bitpath®, the Bitpath Logo®, Sripath Asia-Pac®, the Sripath Asia-Pac Logo®, Sripath Innovations®, the Sripath Innovations Logo®, REJUVN8™, ReGENR8™, Make Asphalt Better®, Make Bitumen Better®, Pioneering Sustainable Roadways®, Bitumen Pathways for the Future®, and the Rocky Asphalt™ and Sandy Asphalt™ Mascots are trademarks and/or service marks of Jay Holding Inc. and/or its affiliates in the United States of America and/or in other countries. All Rights Reserved.

DISCLAIMER: Although all statements and information contained herein are believed to be accurate and reliable, they are presented without guarantee or warranty of any kind, express or implied. Information provided herein does not relieve the recipient or user from the responsibility of carrying out own tests, experiments, and validation. The recipient or user assumes all risks and liability for use of the information and results obtained. Statements or suggestions concerning the use of materials and processes are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all toxicity data and safety measures are indicated herein or that other measures may not be required.

#### **NuMIXER**®

Improve Polymer & Crumb Rubber Compatibility & Dispersion Enhance Low Temperature Properties

Lower & Manage Viscosity

Improve Fracture Toughness & Fatigue Resistance

Stable at Use, Mixing, & Storage Temperatures

Use with a Wide Range of Bitumen Worldwide

Environmentally Friendly Product

Lower Carbon Footprint & Green House Gas Emissions

Low Odor & No VOC

**Exceptional Dosage Efficiency** 

Ship & Use at Ambient Temperature