



# PGXpand®

## Bitumen-Friendly Polymeric Additive



**Paving Applications**



**Roofing Applications**

**PG 64-22** >> **PG 76-22 or PG 82-22**

*Improve the Performance Grade*

**SP 50 °C** >> **SP 70-100 °C**

*Increase the Softening Point*

- Boost the high temperature paving grade of binder
- Improve rutting resistance
- Maintain low temperature performance
- Maintain low viscosity
- Improve workability
- Blend easily into bitumen

- Increase softening point
- Improve adhesion and tack
- Lower viscosity
- Maintain ductility
- Improve productivity
- Reduce SBS content
- Blend easily into bitumen

*Improve the high temperature performance, softening point, and rutting resistance all while lowering costs. PGXpand is highly compatible with a wide range of bitumens from around the world.*

# Unique Polymeric Additive for Every Challenge

PGXpand®, a bitumen-friendly polymer additive, is uniquely designed to allow Polymer Modified Bitumen (PMB) producers to boost the high temperature performance of the binder while maintaining low temperature properties. It minimizes SBS content, improves viscosity, supports higher filler loading, and provides better stability.

Achieve dramatic benefits with a simple low dosage of PGXpand. Lower energy consumption, reduce production and transportation costs, and improve workability. Expect better rutting resistance and fatigue properties.

## PGXpand® Technical Data

Property	Typical Value	
Softening Point Range	135 to 145 °C	275 to 293 °F
Heating Loss	< 0.5%	
Acid Value	1 to 4 mg KOH/g	
Amine Value	0.2 to 4 mg KOH/g	

*All values representative only.*

## Applications

### Paving



- PMB for Hot Mixes
- Hybrid PMB
- High Stiffness Mixes
- Hot Spray Seal
- Repair & Maintenance

### Roofing

- Self-adhered Membranes
- SBS Base & Cap Membranes



**Boost High Temperature Performance Grade  
& Softening Point.  
Deliver Excellent Rutting Resistance  
& Fatigue Properties.**



[Sripath.com](https://Sripath.com)  
Americas & Africa



[Sripathapc.com](https://Sripathapc.com)  
Australia, New Zealand,  
& Asia-Pacific Region



[SripathInnovations.com](https://SripathInnovations.com)  
United Kingdom, European Union,  
& Middle East



[Bitpath.co.in](https://Bitpath.co.in)  
India



COPYRIGHTS: ©-2025 Sripath Technologies®, LLC

TRADEMARKS: Sripath®, Sripath Technologies®, the Sripath Technologies Logo®, ReLIXER®, PGXpand®, PGXtend®, NuMIXER®, ReNUBIT®, SriCote®, KoolTEQ™, PHALANX®, Bitpath®, the Bitpath Logo®, Sripath Asia-Pac®, the Sripath Asia-Pac Logo®, Sripath Innovations®, the Sripath Innovations Logo®, ReJUVN8™, ReGENR8™, Make Asphalt Better®, Make Bitumen Better®, Pioneering Sustainable Roadways®, Bitumen Pathways for the Future®, and the Rocky Asphalt™ and Sandy Asphalt™ Mascots are trademarks and/or service marks of Joy Holding Inc. and/or its affiliates in the United States of America and/or in other countries. All Rights Reserved.

DISCLAIMER: Although all statements and information contained herein are believed to be accurate and reliable, they are presented without guarantee or warranty of any kind, express or implied. Information provided herein does not relieve the recipient or user from the responsibility of carrying out own tests, experiments, and validation. The recipient or user assumes all risks and liability for use of the information and results obtained. Statements or suggestions concerning the use of materials and processes are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all toxicity data and safety measures are indicated herein or that other measures may not be required.